13 5/8"

LA4421
DECORATIVE LUMINAIRE ASSEMBLY

P078LD4NT340K
46W LED PLATFORM
TYPE V DISTRIBUTION
4000K COLOR TEMP

CL
CLEAR POLYCARBONATE LENS

30 5/8"

LED DRIVER
(WIRED @ 120/277V)

4" CAST ALUMINUM POST CUP

3/8-16 SS SET SCREW
(3 REQD EQ SPCD @ 120°)

4S12.188
4"Ø X .188" ROUND, STRAIGHT,
SMOOTH, ALUMINUM SHAFT

12'-0"
TO TOP
OF
SHAFT

CB0101
DECORATIVE CAST
ALUMINUM BASE

32 1/2"

ACCESS HOLE WITH
CAST ALUMINUM DOOR

USE
RM-C BASE PLATE #44

7 3/4"

GROUND LINE

CONDUIT BY OTHERS

CONCRETE FOOTING DESIGNED
AND PROVIDED BY OTHERS

1/2"Ø X 18" GALVANIZED STEEL
ANCHOR BOLT (4 REQ)

PROPORTIONAL VIEW

Ø11 3/4" BASE PLATE

MOUNTING SLOT FOR
1/2"Ø ANCHOR BOLT

Ø8" BOLT CIRCLE

ACCESS HOLE

MOUNTING DETAIL

*UL LISTED