

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



Specifications

Material:
All parts are durable 356 cast aluminum and high strength aluminum spinnings. All hardware provided shall be stainless steel or zinc plated steel.

Fixture Mounting:
Post Mount: Post Cap with set screws. Fits 3" and 4" poles.

Drivers:
Universal voltage 120-277 is standard. 0-10V dimming is standard for LED platforms and 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules.

See page 2 table for LED engine and driver specs, voltage and dimming protocols.

Electrical:
Approximately 12" of pull wire extends from luminaire. Additional pull wire provided for post mount arms and wall mounts.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.

LA211

LED


Dark Sky Friendly

Weight: 25.0 lbs

EPA: 0.63

BUG: *See Table Below

Catalog Logic



Catalog Number	1	2	3	4	5	6	7	8
LA211	1		D					

1	FIXTURE ORIENTATION
1 Post	

2	LIGHT SOURCE & WATTAGES
P029LD4 (29w Platform; 400ma Driver)	
P046LD4 (46w Platform; 400ma Driver)	
M016LD (16w, 2000 lumen, Cree module)	
M024LD (24w, 3000 lumen, Cree module)	

3	DIMMING
D (Dimming)	
See page 2 table for LED engine and driver specs, voltage and dimming protocols.	

4	OPTICS
Platform	Module
T2 (Type II)	W (T5 Wide Distributon with Dome LED Lens)
T3 (Type III)	N (T5 Narrow Distributon with Flat LED Lens)
T5 (Type V)	

*BUG RATING TABLE	
B1-U3-G1	M037LDNW40K
B1-U0-G1	P046LD4NT350K
B1-U0-G1	P046LD4NT550K
B1-U3-G2	P046LD4NT340K-HSS

5	COLOR TEMPERATURE (CCT)	
Platform	Module	
27K (2700K)	27K (2700K)	
30K (3000K)	30K (3000K)	
35K (3500K)	35K (3500K)	
40K (4000K)	40K (4000K)	

6	ACCESSORIES
HSS90 (90° House Side Shield, polished)	
HSS120 (120° House Side Shield, polished)	
*EMG-LED5 (5w, LED Emergency Driver, remote placement, Cree module only)	
*EMG-LED7 (7w, LED Emergency Driver, remote placement, Cree module only)	
*EMG-LED10 (10w, LED Emergency Driver, remote placement, Cree module only)	
*EMG-LED20HV (20w, High Voltage LED Emergency Driver, remote placement, for use with Platforms and Towers, 78w or less)	
HLMSPC-06 (High-Low Motion Sensor/Photocell; 15' - 30' Sensor Mounting Height)	
HLMSPC-10 (High-Low Motion Sensor/Photocell; 8' - 15' Sensor Mounting Height)	
PC (Button Photo Cell)	
SP (Surge Protector, 10kA & 10kV)	
TLPC (Twist Lock photo cell & receptacle)	
TL (Twist Lock receptacle only)	
TL5 (5-pin Twist Lock receptacle only)	
TL7 (7-pin Twist Lock receptacle only)	

*For Emergency lumen output data, see Resources section at www.ANPLighting.com.

7	MOUNTING SOURCE			
	Post Mount Arms *See Page 3 for Style/Size		Wall Mount Arms *See Page 3 for Style/Size	
PA3321	PA8521	WM2141	WM7421	
PA5151	PA8571	WM2211	WM8021	
PA5411		WM3001		
PA5611		WM3351		
PA5621		WM4511		
PA5651		WM5131		
PA6211		WM5161		
PA6311		WM5311		
PA7911		WM5601		
PA8031		WM5611		
	Column Mount *See Page 3 for Style/Size			
CM	Column Mount			

8	FINISHES			
	Standard Grade	Marine Grade	Standard Grade	Marine Grade
40	NA	Raw Unfinished	53	100
41	101	Black	56	109
42	102	Forest Green	61	106
43	114	Bright Red	70	118
44	107	White	71	105
45	112	Bright Blue	72	108
46	123	Sunny Yellow	73	125
47	120	Aqua Green	76	121
49	NA	Galvanized	77	127
50	111	Navy	78	124
51	103	Architectural Bronze	10	130
52	104	Patina Verde	11	131
12	133	Lilac	13	132

Consult factory for additional paint charges and availability

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

LED PERFORMANCE

MODULE					PLATFORM				
LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy	LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
16W	2700K	2000	19W	125	29W	2700K	2670	30w	89
	3000K	2000	19W	125		3000K	2670	30w	89
	3500K	2000	19W	125		3500K	3209	30w	107
	4000K	2000	19W	125		4000K	3465	30w	116
2700K	3000	28W	125	46W		2700K	4004	46w	87
3000K	3000	28W	125		3000K	4004	46w	87	
3500K	3000	28W	125		3500K	4814	46w	105	
4000K	3000	28W	125		4000K	5197	46w	115	

MODULE SPECIFICATION

- Efficacy 65-125 lumens per watt
- Life: L70 50,000 hours
- Color temp: 2700K,3000K,3500K and 4000K
- CRI: >90

MODULE DRIVER SPECIFICATION

- Input Voltage: 120-277 Volts; 50/60Hz
- Dimmable down to 1%
- 0-10V, TRIAC and ELV dimming protocols are standard.
- Output Current: Constant Current: 440mA to 940mA (model dependent)
- Driver Efficiency > 80%; Power Factor > 0.9
- Integral Surge Protection in conformance to ANSI C62.41 Category A

MODULE LISTINGS

- Fully compliant with the RoHS Directive
- Certifications: CE/UL

PLATFORM SPECIFICATION:

- Efficacy ranges from 80-116 lumens per watt
- Customized lens precisely directs the light
- Operating temperature of -30C to 55C
- Life: L70 is 60,000 hours
- PLATFORM CCT: 2700K, 3000K,3500K, and 4000K
- TOWER CCT: 4000K
- CRI: >70
- Parallel circuitry ensures consistent light output in the event of single LED failure

PLATFORM DRIVER SPECIFICATION:

- Operates at 400mA
- Dimmable down to 10%
- Built in surge protection
- Constant current output 50/60HZ
- Driver Efficiency > 90% power factor above 99%
- 120 – 277 volts
- 0-10V dimming protocol is standard

PLATFORM LISTINGS

- Fully compliant with the RoHS Directive
- Certifications: ETL
- Rated IP65 with an optional IP66 rating

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

- 5 year limited warranty on Modules/Drivers
- 7 year limited warranty* on Platform LED engines
- 5 year limited warranty* on Platform Drivers

*Limited Warranty: A typical year is defined as 4380 hours of operation. Failure defined as more than 10% of the total platform LED's not operating.

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

POST MOUNTS - See Post Arm Section on Website for Specification Sheets and additional post arms.
Dimensions are Projection x Height

COLUMN MOUNT



PA3321 / 18" x 14 3/4"



PA5151 / 14 1/4" x 19 3/4"



PA5411 / 17 7/8" x 25 1/8"



PA5611 / 18 5/8" x 26 1/2"



CM / 5 3/4" SQ x 3 1/2" H



PA5621 / 19" x 26 1/4"



PA5651 / 20" x 26 1/4"



PA6211 / 22 3/4" x 26 1/2"




PA6311 / 17" x 23 1/4"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"

WALL MOUNTS - See Wall Mount Section on Website for Specification Sheets and additional wall mount arms.
Dimensions are Projection x Height



WM2141 / 18" x 12 3/16"



WM2211 / 15 1/2" x 15 7/8"



WM3001 / 11" x 8 7/8"



WM3351 / 14 1/2" x 17"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5311 / 10 7/8" x 10"



WM5601 / 17 7/8" x 14"



WM5611 / 17 5/8" x 22"



WM7421 / 16 3/8" x 15 3/4"



WM8021 / 19 1/4" x 16 3/8"

ACCESSORIES



HSS90 & HSS120



EMG-LED5, 7, 10 & 20HV



HLMSPC-06 & HLMSPC-10



PC



TLPC



TL



TL5 & TL7