

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

Specifications

Material:
All parts are durable 356 cast aluminum and high strength aluminum spinnings. All mounting hardware shall be stainless steel or zinc plated steel.

Lens:
Standard acrylic lens.

Fixture Mounting:
Post Mount: Post Cap with set screws. Fits 3" and 4" poles.

Drivers:
Universal voltage 120-277 is standard. 0-10V dimming is standard for LED platforms and towers. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules.

See page 2 table for LED engine and driver specs, voltage and dimming protocols.

Electrical:
Approximately 12" of pull wire extends from luminaire. Additional pull wire provided for post mount arms and wall mounts.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.


Modifications:
Consult factory for custom or modified designs.



LA513 LED

Weight: 34.0 lbs
EPA: 3.0

Catalog Logic



| Catalog Number | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|----------------|---|---|---|---|---|---|---|---|
| LA513 | 1 | | | | | | | |

1 FIXTURE ORIENTATION

| |
|--------|
| 1 Post |
|--------|

2 LENS

| |
|-------------------------|
| CL (Clear Acrylic) |
| FR (Frosted Acrylic) |
| WH (White Opal Acrylic) |

3 LIGHT SOURCE & WATTAGES

| |
|----------------------------------------|
| P029LD4D (29w Platform; 400ma Driver) |
| P046LD4D (46w Platform; 400ma Driver) |
| P078LD4D (78w Platform; 400ma Driver) |
| M016LDD (16w, 2000 lumen, Cree module) |
| M024LDD (24w, 3000 lumen, Cree module) |
| M037LDD (37w, 4000 lumen, Cree module) |

4 OPTICS

| Platform | Module |
|---------------|-----------------------------------------------|
| T2 (Type II) | W (T5 Wide Distribution with Dome LED Lens) |
| T3 (Type III) | N (T5 Narrow Distribution with Flat LED Lens) |
| T5 (Type V) | |

5 COLOR TEMPERATURE (CCT)

| Platform | Module |
|-------------|-------------|
| 27K (2700K) | 27K (2700K) |
| 30K (3000K) | 30K (3000K) |
| 35K (3500K) | 35K (3500K) |
| 40K (4000K) | 40K (4000K) |

6 ACCESSORIES

| |
|--------------------------------------------------------------------------------------------------------------|
| CHC (Clear Glass Chimney) |
| CHF (Frosted Glass Chimney) |
| HSS90 (90° House Side Shield, polished) |
| HSS120 (120° House Side Shield, polished) |
| *EMG-LED5 (5w, LED Emergency Driver, remote placement, Cree module only) |
| *EMG-LED7 (7w, LED Emergency Driver, remote placement, Cree module only) |
| *EMG-LED10 (10w, LED Emergency Driver, remote placement, Cree module only) |
| *EMG-LED20HV (20w, High Voltage LED Emergency Driver, remote placement, for use with Platforms, 78w or less) |
| HLMSPC-06 (High-Low Motion Sensor/Photocell; 15' - 30' Sensor Mounting Height) |
| HLMSPC-10 (High-Low Motion Sensor/Photocell; 8' - 15' Sensor Mounting Height) |
| PC (Button Photo Cell) |
| SP (Surge Protector, 10kA & 10kV) |
| TLPC (Twist Lock photo cell, includes receptacle & photo cell) |
| TL5 (5-pin Twist Lock receptacle) |
| TL7 (7-pin Twist Lock receptacle) |

*For Emergency lumen output data, see Resources section at www.ANPlighting.com.

**Accessory finish will match fixture finish.

7 MOUNTING SOURCE

| Post Mount Arms *See Page 3 for Style/Size | | Wall Mount Arms *See Page 3 for Style/Size | |
|-----------------------------------------------|--------------|-----------------------------------------------|--------|
| PA3111 | PA8521 | WM2141 | WM8581 |
| PA3321 | PA8571 | WM2211 | WM8831 |
| PA5151 | | WM2221 | |
| PA5171 | | WM4511 | |
| PA5411 | | WM5131 | |
| PA6111 | | WM5161 | |
| PA6211 | | WM5601 | |
| PA7711 | | WM6111 | |
| PA7911 | | WM7411 | |
| PA8031 | | WM7421 | |
| Column Mount *See Page 3 for Style/Size | | | |
| CM | Column Mount | | |

8 FINISHES
*Premium and Marine Grade Finish have additional charges

| Standard Colors | Standard Grade | Marine Grade* | Standard Colors | Standard Grade | Marine Grade* |
|-----------------|----------------|---------------|-------------------------------|----------------|---------------|
| Aspen Green | 10 | 10M | Architectural Bronze | 51 | 51M |
| Cantaloupe | 11 | 11M | Patina Verde | 52 | 52M |
| Lilac | 12 | 12M | Copper Clay | 53 | 53M |
| Putty | 13 | 13M | Silver | 56 | 56M |
| Raw Unfinished | 40 | NA | Black Verde | 61 | 61M |
| Black | 41 | 41M | Painted Chrome | 70 | 70M |
| Forest Green | 42 | 42M | Painted Copper | 71 | 71M |
| Bright Red | 43 | 43M | Textured Black | 72 | 72M |
| White | 44 | 44M | Matte Black | 73 | 73M |
| Bright Blue | 45 | 45M | Textured Architectural Bronze | 76 | 76M |
| Sunny Yellow | 46 | 46M | Textured White | 77 | 77M |
| Aqua Green | 47 | 47M | Textured Silver | 78 | 78M |
| Galvanized | 49 | NA | PREMIUM FINISH | Premium Grade* | Marine Grade* |
| Navy | 50 | 50M | Carbon Graphite | 96 | 96M |

Consult Factory for additional paint charges and availability.

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

LED PERFORMANCE

| MODULE | | | | |
|-------------|-------|-----------------------|----------------|------------------|
| LED Wattage | CCT | Typical Luminous Flux | System Wattage | Typical Efficacy |
| 16W | 2700K | 2000 | 19W | 125 |
| | 3000K | 2000 | 19W | 125 |
| | 3500K | 2000 | 19W | 125 |
| | 4000K | 2000 | 19W | 125 |
| 24W | 2700K | 3000 | 28W | 125 |
| | 3000K | 3000 | 28W | 125 |
| | 3500K | 3000 | 28W | 125 |
| | 4000K | 3000 | 28W | 125 |
| 37W | 2700K | 4000 | 43W | 108 |
| | 3000K | 4000 | 43W | 108 |
| | 3500K | 4000 | 43W | 108 |
| | 4000K | 4000 | 43W | 108 |

| PLATFORM | | | | |
|-------------|-------|-----------------------|----------------|------------------|
| LED Wattage | CCT | Typical Luminous Flux | System Wattage | Typical Efficacy |
| 29W | 2700K | 2670 | 30w | 89 |
| | 3000K | 2670 | 30w | 89 |
| | 3500K | 3209 | 30w | 107 |
| | 4000K | 3465 | 30w | 116 |
| 46W | 2700K | 4004 | 46w | 87 |
| | 3000K | 4004 | 46w | 87 |
| | 3500K | 4814 | 46w | 105 |
| | 4000K | 5197 | 46w | 115 |
| 78W | 2700K | 7041 | 80w | 88 |
| | 3000K | 7041 | 80w | 88 |
| | 3500K | 8464 | 80w | 106 |
| | 4000K | 9138 | 80w | 114 |

PLATFORM SPECIFICATION:

- Efficacy ranges from 87-116 lumens per watt
- Customized lens precisely directs the light
- Operating temperature of -30C to 55C
- Life: L70 is 60,000 hours
- PLATFORM CCT: 2700K, 3000K, 3500K, and 4000K
- CRI: >70
- Parallel circuitry ensures consistent light output in the event of single LED failure

PLATFORM DRIVER SPECIFICATION:

- Operates at 400mA
- Dimmable down to 10%
- Built in surge protection
- Constant current output 50/60HZ
- Driver Efficiency > 90% power factor above 99%
- 120 – 277 volts
- 0-10V dimming protocol is standard

PLATFORM LISTINGS

- Fully compliant with the RoHS Directive
- Certifications: ETL
- Rated IP65 with an optional IP66 rating

MODULE SPECIFICATION:

- Efficacy 108-125 lumens per watt
- Life: L70 50,000 hours
- Color temp: 2700K, 3000K, 3500K and 4000K
- CRI: >90

MODULE DRIVER SPECIFICATION:

- Input Voltage: 120-277 Volts; 50/60Hz
- Dimmable down to 1%
- 0-10V, TRIAC and ELV dimming protocols are standard.
- Output Current: Constant Current; 440mA to 940mA (model dependent)
- Driver Efficiency > 80%; Power Factor > 0.9
- Integral Surge Protection in conformance to ANSI C62.41 Category A.

MODULE LISTINGS

- Fully compliant with the RoHS Directive
- Certifications: CE/UL







WARRANTY

See www.ANPlighting.com for complete fixture warranty.

- 5 year limited warranty on Modules/Drivers
- 7 year limited warranty* on Platform LED engines
- 5 year limited warranty* on Platform Drivers

*Limited Warranty: A typical year is defined as 4380 hours of operation. Failure defined as more than 10% of the total platform LED's not operating

ACCESSORIES

| | | | | | |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
|  |  |  |  |  |  |
| HSS90 & HSS120 | EMG-LED5, 7, 10 & 20HV | HLMSPC-06 & HLMSPC-10 | PC | TLPC | TL5 & TL7 |


Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

POST MOUNTS - See Post Arm Section on Website for Specification Sheets and additional post arms.
 Dimensions are Projection x Height

COLUMN MOUNT



CM / 5 3/4" SQ x 3 1/2" H



PA3111 / 25" x 15 1/4"



PA3321 / 18" x 14 3/4"



PA5151 / 14 1/4" x 19 3/4"



PA5171 / 15 1/4" x 25 5/8"



PA5411 / 17 7/8" x 25 1/8"




PA6111 / 20 1/2" x 25 1/8"



PA6211 / 22 3/4" x 26 1/2"



PA7711 / 13 1/8" x 21 1/2"



PA7911 / 20" x 20 5/8"



PA8031 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8571 / 24" x 47"

WALL MOUNTS - See Wall Mount Section on Website for Specification Sheets and additional wall mount arms.
 Dimensions are Projection x Height.



WM2141 / 18" x 12 3/16"



WM2211 / 15 1/2" x 15 7/8"



WM2221 / 13 1/2" x 13 1/4"



WM4511 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5161 / 15 3/4" x 17 3/4"



WM5601 / 17 7/8" x 14"




WM6111 / 20 3/8" x 24"



WM7411 / 14" x 15 3/4"



WM7421 / 16 3/8" x 15 3/4"



WM8581 / 17 1/8" x 17 1/2"



WM8831 / 17 1/4" x 16 3/8"