


Quick Ship

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



Specifications

Material:
All parts are durable 356 cast aluminum and high strength aluminum spinnings. All hardware provided shall be stainless steel or zinc plated steel.

Fixture Mounting:
Pendant Mount: Pin mount to tenon. Fits 3" and 4" poles.

Drivers:
Universal voltage 120-277 is standard. 0-10V dimming is standard for LED platforms.

See page 2 table for LED engine and driver specs, voltage and dimming protocols.

Electrical:
Approximately 12" of pull wire extends from luminaire. Additional pull wire provided for post mount arms and wall mounts.



Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.

Q-BVA2001

LED

Dark Sky Friendly.

Weight: 6.5 lbs

EPA: 0.86

Catalog Logic						
Q-BVA2001	P046LD4	D	T5	40K	UNV	76
Luminaire Series	Light Source & Wattage	Dimming	Optic	CCT	Voltage	Finish

Catalog Number						
1	2	3	4	5	6	
Q-BVA2001	P046LD4	D	T5	40K	UNV	76

1	LIGHT SOURCE & WATTAGES
P029LD4	(29w Platform, 400ma Driver)
P046LD4	(46w Platform; 400ma Driver)
P078LD4	(78w Platform; 400ma Driver)
P117LD4	(117w Platform; 400ma Driver)

2	DIMMING
D	(Dimming)
See page 2 table for LED engine and driver specs, voltage and dimming protocols.	

3	OPTICS
T2	(Type II)
T3	(Type III)
T5	(Type V)

4	COLOR TEMPERATURE (CCT)
27K	(2700K)
30K	(3500K)
35K	(3500K)
40K	(4000K)

5	VOLTAGE
UNV	(120-277)

6 FINISHES					
Standard Grade	Marine Grade		Standard Grade	Marine Grade	
40	NA	Raw Unfinished	53	100	Copper Clay
41	101	Black	56	109	Silver
42	102	Forest Green	61	106	Black Verde
43	114	Bright Red	70	118	Painted Chrome
44	107	White	71	105	Painted Copper
45	112	Bright Blue	72	108	Textured Black
46	123	Sunny Yellow	73	125	Matte Black
47	120	Aqua Green	76	121	Textured Architectural Bronze
49	NA	Galvanized	77	127	Textured White
50	111	Navy	78	124	Textured Silver
51	103	Architectural Bronze	10	130	Aspen Green
52	104	Patina Verde	11	131	Cantaloupe
12	133	Lilac	13	132	Putty

Consult factory for additional paint charges and availability

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

LED PERFORMANCE				
PLATFORM				
LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
29W	2700K	2670	30w	89
	3000K	2670	30w	89
	3500K	3209	30w	107
	4000K	3465	30w	116
46W	2700K	4004	46w	87
	3000K	4004	46w	87
	3500K	4814	46w	105
	4000K	5197	46w	115
78W	2700K	7041	80w	88
	3000K	7041	80w	88
	3500K	8464	80w	106
	4000K	9138	80w	114
117W	2700K	10561	120w	88
	3000K	10561	120w	88
	3500K	12696	120w	106
	4000K	13707	120w	114

- PLATFORM SPECIFICATION:**
- Efficacy ranges from 80-116 lumens per watt
 - Customized lens precisely directs the light
 - Operating temperature of -30C to 55C
 - Life: L70 is 60,000 hours
 - PLATFORM CCT: 2700K, 3000K, 3500K, and 4000K
 - TOWER CCT: 4000K
 - CRI: >70
 - Parallel circuitry ensures consistent light output in the event of single LED failure

- PLATFORM DRIVER SPECIFICATION:**
- Operates at 400mA
 - Dimmable down to 10%
 - Built in surge protection
 - Constant current output 50/60HZ
 - Driver Efficiency > 90% power factor above 99%
 - 120 – 277 volts
 - 0-10V dimming protocol is standard

- PLATFORM LISTINGS**
- Fully compliant with the RoHS Directive
 - Certifications: ETL
 - Rated IP65 with an optional IP66 rating

WARRANTY

See www.anplighting.com for complete fixture warranty.

- 7 year limited warranty* on Platform LED engines
- 5 year limited warranty* on Platform Drivers

*Limited Warranty: A typical year is defined as 4380 hours of operation. Failure defined as more than 10% of the total platform LED's not operating.