


# Specifications D618-42WPL-RTC-200GLFR-GUP-E6

Project: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Customer: \_\_\_\_\_



## Specifications

**Material:**  
 RLM shades are constructed of heavy duty spun aluminum. Wall back plate and ballast housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

**Glass:**  
 Choice of clear, frosted or prismatic glass.

**Ballasts:**  
 Fluorescent Ballast will be electronic. Fluorescent sockets will be 4 pin to accept quad or triple tube lamps.

**Electrical:**  
 4-Pin Socket; Multi-tap 120v, 208v, 240v & 277v.

**Finish:**  
 A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

**Certifications:**  
 Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations.

**Modifications:**  
 Consult factory for custom or modified luminaires.

**D618  
 CFL**

Weight: 2.5 lbs



Catalog Number	1	2	3	4	5	6	7
<b>D618</b>	<b>42WPL</b>	<b>RTC</b>	<b>200GLFRGUP</b>	<b>E6</b>			

1	LIGHT SOURCE & WATTAGES
	Flourescent (CFL)
	GU24 Socket Option
	26WPL
	32WPL
	<b>42WPL</b> (100GL or AC glass not available)
	26CFLDIM
	32CFLDIM
	42CFLDIM (100GL or AC glass not available)
	(Compact Fluorescent dimming is 0-10v and ballast must be located within 12" of lamp)

2	BALLAST HOUSING
	Flourescent (CFL)
	<b>RTC</b> (CFL Ballast Canopy)
	RTCNC (CFL Ballast Canopy/No Spun Cover)
	DBH (Dimming CFL Ballast Housing)

3	GLASS & GUARD
	Up to 100w Options
	100GLCL (Clear Glass)
	100GLFR (Frosted Glass)
	100GLPR (Prismatic Glass)
	100GLCLGUP (Clear Glass & Small Wire Guard)
	100GLFRGUP (Frosted Glass & Small Wire Guard)
	100GLPRGUP (Prismatic Glass & Small Wire Guard)
	100GLCLGUPC (Clear Glass & Cast Guard)
	100GLFRGUPC (Frosted Glass & Cast Guard)
	100GLPRGUPC (Prismatic Glass & Cast Guard)
	100GLGUP (Small Wire Guard with No Glass)
	100GLGUPC (Cast Guard with No Glass)
	AC (Stipple Glass Acorn)
	100GLBG (White Ball Glass)
	Up to 200w Options
	200GLCL (Clear Glass)
	200GLFR (Frosted Glass)
	200GLPR (Prismatic Glass)
	200GLCLGUP (Clear Glass & Large Wire Guard)
	<b>200GLFRGUP</b> (Frosted Glass & Large Wire Guard)
	200GLPRGUP (Prismatic Glass & Large Wire Guard)
	200GLCLGUPC (Clear Glass & Large Cast Guard)
	200GLFRGUPC (Frosted Glass & Large Cast Guard)
	200GLPRGUPC (Prismatic Glass & Large Cast Guard)
	200GLGUP (Large Wire Guard with No Glass)
	200GLGUPC (Large Cast Guard with No Glass)

4	MOUNTING SOURCES
	Arm Mounts (Cast Back Plate (CB) Included)
	E3 E4 E5 <b>E6</b> E8 E9
	E10 E11 E12 E13 E18
	E19 E25
	(See Step 2 for Ballast Housing Options)
	Wall Mounts
	WM40
	WM54
	WM74 (CFL Only)
	WM75 (HID Only)
	WM317 (CFL Only)
	WM84
	Post Mounts (Postline ballast only; 4" OD pole required)
	PM10
	PM20
	PM30
	PM40
	PM50
	PM319
	Cord Mounts
	BLC (8' black cord with 1" x 5 3/8" canopy)
	WHC (8' white cord with 1" x 5 3/8" canopy)
	Stem Mounts
	1/2" (13/16" OD Rigid Stems with STC Flat Canopy)
	2ST6 2ST12 2ST18 2ST24 2ST36 2ST48
	2ST60 2ST72 2ST96
	3/4" (1" OD Rigid Stems with STC Flat Canopy)
	3ST6 3ST12 3ST18 3ST24 3ST36 3ST48
	3ST60 3ST72 3ST96
	(See Step 2 for Ballast Housing Options)

# Specifications D618-42WPL-RTC-200GLFR-GUP-E6

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

5 ACCESSORIES	
CBC	(Cast back plate Spun Alum Cover)
GR18	(18" Wire Grill)
PC	(Button Photo Cell) Remote Only
SC	(Scroll for Arms)
SLC	(Sloped Ceiling Mount, 20° Max)
SQ	(Square Back Plate)
SWL	(Swivel)
TBK	(Turnbuckle Kit)

6 VOLTAGES			
120	208	240	277

**WARRANTY**  
See [www.anplighting.com](http://www.anplighting.com) for complete fixture warranty.

7 FINISHES			
Standard Shade	Matte Shade	Standard Shade	Matte Shade
40	NA Pear Unfinished	88	100 Copper Gray
41	101 Black	89	101 Silver
42	102 Forest Green	91	102 Black Vinyl
43	114 Bright Red	79	110 Paints-Cherry
44	107 White	71	108 Paints-Copper
45	113 Bright Blue	72	109 Textured Black
46	125 Sunny Yellow	75	120 Matte Black
47	126 Aspen Green	76	121 Textured Architectural Bronze
48	NA Silverbrush	77	127 Textured White
50	111 Navy	79	124 Textured Silver
51	105 Architectural Bronze	10	106 Aspen Green
52	104 Paints-Vinyl	11	101 Curlirope
52	106 Lila	10	102 Polly
Premium Shade	Matte Shade	Premium Shade	Matte Shade
81	128 Espresso Chrome	84	116 Candy Apple Red
82	117 Textured Desert Stone	85	122 Cobalt Blue
87	110 Bullmoorish	82	120 Singapore
88	115 Caramel	86	114 Starburst Gray
89	120 Black Silver	88	124 88 Refined Bronze

Consult factory for additional paint colors and availability














# Specifications D618-42WPL-RTC-200GLFR-GUP-E6

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_









## ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms

 E3   32" x 11 7/8"	 E4   26" x 14"	 E5   37" x 16 1/2"	 E6   26" x 9 1/4"
 E8   29 1/4" x 12 1/2"	 E9   28" x 40 5/8"	 E10   52 1/4" x 18"	 E11   35 1/4" x 17 1/4"
 E12   37 3/8" x 2"	 E13   34" x 34 3/8"	 E18   27 3/4" x 21 3/8"	 E19   22 3/4" x 95 1/8"
 E25   23" x 5 1/4"			

## WALL MOUNTS | Dimensions are Projection x Height | POST MOUNTS | Dimensions are Projection x Height











 WM40   13 7/8" x 14 3/4"	 WM54   23 3/8" x 14 1/4"	 PM10   14 1/2" x 25"	 PM20   30 1/8" x 25"
 WM74   22" x 26 1/2" (CFL Only)	 WM75   25" x 26 1/2" (HID Only)	 PM30   21 5/8" x 28 7/8"	 PM40   43 3/8" x 28 7/8"
 WM84   26 1/2" x 57 1/4"	 WM317   15" x 12" (CFL Only)	 PM50   27" x 38"	 PM319   16 5/8" x 27 1/2"

## ACCESSORIES

 CBC	 GR18	 PC	 SC
 SLC	 SQ	 SWL	 TBK

## GLASS & GUARDS

Glass Legend: CL = Clear FR = Frosted PR = Prismatic

Glass Only	
	GLCL GLFR GLPR
	AC (Acorn Glass -- Clear Stipple Only)
	GLBG (Ball Glass -- White Only)
Glass with Cast Guard	
	GLCLGUPC GLFRGUPC GLPRGUPC
Glass with Wire Guard	
	GLCLGUP GLFRGUP GLPRGUP
Guards Only	
	GLGUPC (Cast Guard)
	GLGUP (Wire Guard)
Ballast & Driver Housing	
	RTC
	RTCNC
	DBH