

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____



Specifications

Material:
 RLM shades are constructed of heavy duty spun aluminum. Wall back plate and ballast housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

Finish:
 A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.


Glass:
 Choice of clear, frosted or prismatic glass.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Electrical:
 Medium Base Socket, 200w Maximum.

Certifications:
 Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations.

Modifications:
 Consult factory for custom or modified luminaires.



R916
200w max Incandescent

Weight: 2.0 lbs

Catalog Logic: **R916** - **BLC** - **N.A.** - **N.A.** - **41**

R916: RLM Style
 BLC: Mounting Source
 N.A.: Glass & Guards
 N.A.: Accessories
 41: Finish

Catalog Number: **1** **2** **3** **4**

R916 - **BLC** - **N.A.** - **N.A.**

1 MOUNTING SOURCES	
Arm Mounts (Cast back plate included)	
E3 E4 E6 E7 E8 E9	
E10 E11 E12 E13 E18	
E20 E22 E23 E25 E26	
Wall Mounts	
WM10	
WM35	
WM40	
WM55	
WM75	
WM318	
Post Mounts	
PM10	
PM20	
PM30	
PM40	
PM50	
PM319	
Cord Mounts	
BLC (6' black cord with 1" x 5 3/8" canopy)	
WHC (6' white cord with 1" x 5 3/8" canopy)	
Stem Mounts	
1/2" (13/16" OD Rigid Stems with STC Flat Canopy)	
2ST6 2ST12 2ST18 2ST24 2ST36 2ST48	
2ST60 2ST72 2ST96	
3/4" (1" OD Rigid Stems with STC Flat Canopy)	
3ST6 3ST12 3ST18 3ST24 3ST36 3ST48	
3ST60 3ST72 3ST96	

2 GLASS & GUARD	
Up to 100w Options	
100GLCL (Clear Glass)	
100GLFR (Frosted Glass)	
100GLPR (Prismatic Glass)	
100GLCLGUP (Clear Glass & Small Wire Guard)	
100GLFRGUP (Frosted Glass & Small Wire Guard)	
100GLPRGUP (Prismatic Glass & Small Wire Guard)	
100GLCLGUPC (Clear Glass & Cast Guard)	
100GLFRGUPC (Frosted Glass & Cast Guard)	
100GLPRGUPC (Prismatic Glass & Cast Guard)	
100GLGUP (Small Wire Guard with No Glass)	
100GLGUPC (Cast Guard with No Glass)	
AC (Stipple Glass Acorn)	
100GLBG (White Ball Glass)	
Up to 200w Options	
200GLCL (Clear Glass)	
200GLFR (Frosted Glass)	
200GLPR (Prismatic Glass)	
200GLCLGUP (Clear Glass & Large Wire Guard)	
200GLFRGUP (Frosted Glass & Large Wire Guard)	
200GLPRGUP (Prismatic Glass & Large Wire Guard)	
200GLCLGUPC (Clear Glass & Large Cast Guard)	
200GLFRGUPC (Frosted Glass & Large Cast Guard)	
200GLPRGUPC (Prismatic Glass & Large Cast Guard)	
200GLGUP (Large Wire Guard with No Glass)	
200GLGUPC (Large Cast Guard with No Glass)	

3 ACCESSORIES	
CBC	(Cast back plate Spun Alum Cover)
PC	(Button Photo Cell) Remote Only
SC	(Scroll for Arms)
SLC	(Sloped Ceiling Mount, 20° Max)
SQ	(Square Back Plate)
SWL	(Swivel)
TBK	(Turnbuckle Kit)

4 FINISHES					
Standard Grade	Marine Grade		Standard Grade	Marine Grade	
40	NA	Raw Unfinished	53	100	Copper Clay
41	101	Black	56	109	Silver
42	102	Forest Green	61	106	Black Verde
43	114	Bright Red	70	118	Painted Chrome
44	107	White	71	105	Painted Copper
45	112	Bright Blue	72	108	Textured Black
46	123	Sunny Yellow	73	125	Matte Black
47	120	Aqua Green	76	121	Textured Architectural Bronze
49	NA	Galvanized	77	127	Textured White
50	111	Navy	78	124	Textured Silver
51	103	Architectural Bronze	10	130	Aspen Green
52	104	Patina Verde	11	131	Cantaloupe
Premium Grade	Marine Grade		Premium Grade	Marine Grade	
81	129	Extreme Chrome	64	116	Candy Apple Red
80	117	Textured Desert Stone	65	122	Cobalt Blue
67	119	Butterscotch	82	128	Graystone
66	115	Caramel	69	113	Gunmetal Gray
68	126	Black Silver	83	134	Oil Rubbed Bronze

Consult factory for additional paint charges and availability

WARRANTY
 See www.anplighting.com for complete fixture warranty.

Project: _____


Fixture Type: _____ Quantity: _____

Customer: _____








ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms

 E3 32" x 11 7/8"	 E4 26" x 14"	 E5 37" x 16 1/2"	 E6 26" x 9 1/4"
 E8 29 1/4" x 12 1/2"	 E9 28" x 40 5/8"	 E10 52 1/4" x 18"	 E11 35 1/4" x 17 1/4"
 E12 37 3/8" x 2"	 E13 34" x 34 3/8"	 E15 13 3/8" x 10 1/2"	 E18 27 3/4" x 21 3/8"
 E19 22 3/4" x 95 1/8"	 E25 23" x 5 1/4"	 E26 8 1/8" x 6"	

WALL MOUNTS | Dimensions are Projection x Height | **POST MOUNTS** | Dimensions are Projection x Height

 WM10 15 3/4" x 13 3/4"	 WM35 20 1/2" x 25"	 PM10 14 1/2" x 25"	 PM20 30 1/8" x 25"
 WM40 13 7/8" x 14 3/4"	 WM55 20 5/8" x 14 1/4"	 PM30 21 5/8" x 28 7/8"	 PM40 43 3/8" x 28 7/8"
 WM75 25" x 26 1/2"	 WM318 12" x 12 3/4"	 PM50 27" x 38"	 PM319 16 5/8" x 27 1/2"

ACCESSORIES

 CBC	 PC	 SC	 SLC
 SQ	 SWL	 TBK	

GLASS & GUARDS

Glass Legend: CL = Clear FR = Frosted PR = Prismatic	
Glass Only	
	GLCL GLFR GLPR
	AC (Acorn Glass -- Clear Stipple Only)
	GLBG (Ball Glass -- White Only)
Glass with Cast Guard	
	GLCLGUPC GLFRGUPC GLPRGUPC
Glass with Wire Guard	
	GLCLGUP GLFRGUP GLPRGUP
Guards Only	
	GLGUPC (Cast Guard)
	GLGUP (Wire Guard)