


Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



Specifications

Material:
Constructed of complete cast aluminum. All hardware provided shall be stainless steel. Screw hardware may not match paint.

Glass:
Choice of clear, frosted or prismatic glass. Colored glass available for extra charge.

Electrical:
GU24 socket, 120V only. Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming protocols are standard for LED modules. (12w is TRIAC dimming & 120v only; 24w is 0-10v only)

See page 2 table for LED module and driver specs, voltage and dimming protocols.



Certifications:
Cord mounts are UL Listed for dry locations. Arm, wall, post, pendant and stem mounts are UL Listed for wet locations.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.


Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.

VTP200GL LED

Weight: 5 lbs

Catalog Logic



Catalog Number	1	2	3	4	5	6	7	8	9	10	11	12
	VTP200GL	CL	M024LD	D	W	40K	RTCNC	E22	GUP	VTS	PC	UNV

1	GLASS
NA	(No Glass)
CL	(Clear Glass)
FR	(Frosted Glass)
PR	(Prismatic Glass)
BLU	(Blue Glass)
AMB	(Amber Glass)
GRN	(Green Glass)
RED	(Red Glass)
BG	(Ball Glass -- White Only)

2	LIGHT SOURCE & WATTAGES
GU24	(GU24 Socket Only, 120V only)
M012LD	(12w, 750 lumen, Cree module) Integral driver, 120V, TRIAC dimming & narrow distribution only.
M009LD	(9w, 850 lumen, Cree module)
M010LD	(10w, 1250 lumen, Cree module)
M016LD	(16w, 2000 lumen, Cree module)
M024LD	(24w, 3000 lumen, Cree module)

3	DIMMING
D	(Dimming)

See page 2 table for LED engine and driver specs, voltage and dimming protocols.

4	DISTRIBUTION
W	(T5 Wide Distribution with Dome LED Lens)
N*	(T5 Narrow Distribution with Flat LED Lens)

*12w is narrow only, select "N".

5	COLOR TEMPERATURE (CCT)
27K	(2700K)
30K	(3000K) (Not Sunset Dim)
35K	(3500K) (Not Sunset Dim)
40K	(4000K) (Not Sunset Dim)

6	DRIVER HOUSING
RTC	(Driver Canopy)
RTCNC	(Driver Canopy/No Spun Cover)
NA	(Housing not required for 12w)

7	MOUNTING SOURCES
Arm Mounts (Cast back plate included)	
E6 E9 E13 E22 E23 E24 E25 E26 E27 E36 E39	
Wall Mounts	
WM35	
WM40	
WM318	
Post Mounts	
PM10	
PM20	
Pendant Mounts	
2 Light Pendant 100w Vapor Tights	
21PEND6 21PEND12 21PEND18 21PEND24 21PEND36	
21PEND48 21PEND60 21PEND72 21PEND96	
3 Light Pendant 100w Vapor Tights	
31PEND6 31PEND12 31PEND18 31PEND24 31PEND36	
31PEND48 31PEND60 31PEND72 31PEND96	
4 Light Pendant 100w Vapor Tights	
41PEND6 41PEND12 41PEND18 41PEND24 41PEND36	
41PEND48 41PEND60 41PEND72 41PEND96	
Cord Mounts	
BLC	(6' black cord with 1" x 5 3/8" canopy)
WHC	(6' white cord with 1" x 5 3/8" canopy)
Stem Mounts	
3/4"	(1"OD Rigid Stems with STC Flat Canopy)
3ST6 3ST12 3ST18 3ST24 3ST36 3ST48	
3ST60 3ST72 3ST96	

8	GUARD
NA	(No Guard)
GUP	(Wire Guard)
GUPC	(Cast Guard)

9	SHADE ACCESSORIES
NA	(No Accessory)
VTS	(9 3/4" Angle Ring)

10	ACCESSORIES
CBC	(Cast back plate Spun Alum Cover)
PC	(Button Photo Cell) Remote Only
SC	(Scroll for Arms)
SLC	(Sloped Ceiling Mount, 20° Max)
SQ	(Square Back Plate)
SWL	(Swivel)
TBK	(Turnbuckle Kit)

11	VOLTAGE
UNV	(120-277)

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

12 FINISHES					
Standard Grade	Marine Grade		Standard Grade	Marine Grade	
40	NA	Raw Unfinished	53	100	Copper Clay
41	101	Black	56	109	Silver
42	102	Forest Green	61	106	Black Verde
43	114	Bright Red	70	118	Painted Chrome
44	107	White	71	105	Painted Copper
45	112	Bright Blue	72	108	Textured Black
46	123	Sunny Yellow	73	125	Matte Black
47	120	Aqua Green	76	121	Textured Architectural Bronze
49	NA	Galvanized	77	127	Textured White
50	111	Navy	78	124	Textured Silver
51	103	Architectural Bronze	10	130	Aspen Green
52	104	Patina Verde	11	131	Cantaloupe
12	133	Lilac	13	132	Putty
Premium Grade	Marine Grade		Premium Grade	Marine Grade	
81	129	Extreme Chrome	64	116	Candy Apple Red
80	117	Textured Desert Stone	65	122	Cobalt Blue
67	119	Butterscotch	82	128	Graystone
66	115	Caramel	69	113	Gunmetal Gray
68	126	Black Silver			

Consult factory for additional paint charges and availability

LED PERFORMANCE				
MODULE				
LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
9W	2700K	850	11W	97
	3000K	850	11W	97
	3500K	850	11W	97
	4000K	850	11W	97
10W	2700K	1250	12W	125
	3000K	1250	12W	125
	3500K	1250	12W	125
	4000K	1250	12W	125
12W	2700K	750	12W	65
	3000K	750	12W	65
	3500K	750	12W	65
	4000K	750	12W	65
16W	2700K	2000	19W	125
	3000K	2000	19W	125
	3500K	2000	19W	125
	4000K	2000	19W	125
24W	2700K	3000	28W	125
	3000K	3000	28W	125
	3500K	3000	28W	125
	4000K	3000	28W	125

MODULE SPECIFICATION
<ul style="list-style-type: none"> Efficacy 65-125 lumens per watt Dimmable down to 1% Life: L70 50,000 hours Color temp: 2700K,3000K,3500K and 4000K CRI: >90

MODULE DRIVER SPECIFICATION
<ul style="list-style-type: none"> Input Voltage: 120-277 Volts; 50/60Hz 0-10V, TRIAC and ELV dimming protocols are standard. (24w is 0-10v only) Output Current: Constant Current: 440mA to 940mA (model dependent) Driver Efficiency > 80%; Power Factor > 0.9 Integral Surge Protection in conformance to ANSI C62.41 Category A

MODULE LISTINGS
<ul style="list-style-type: none"> Fully compliant with the RoHS Directive Certifications: CE/UL

WARRANTY
<p>See www.anplighting.com for complete fixture warranty.</p> <p>LED warranty information</p> <ul style="list-style-type: none"> 5 year limited warranty* <p>*Limited Warranty: A typical year is defined as 4380 hours of operation.</p>

Project: _____






Fixture Type: _____ Quantity: _____

Customer: _____

ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms

 E6 26 1/8" x 9 1/4"	 E9 28" x 40 5/8"	 E13 34" x 34 3/8"	 E22 7 1/2" x 2"
 E23 6" x 2" x 11 1/2"	 E24 10" x 2"	 E25 23" x 5 1/4"	 E26 8 1/8" x 6"
 E27 10" x 2"	 E36 20 1/4" x 8"	 E39 10 1/2" x 15 1/8"	


WALL MOUNTS | Dimensions are Projection x Height | **POST MOUNTS** | Dimensions are Projection x Height

 WM35 20 1/2" x 25"	 WM40 13 7/8" x 14 3/4"	 PM10 14 1/2" x 25"	 PM20 30 1/8" x 25"
 WM318 12" x 12 3/4"			








PENDANT MOUNTS | xx is Height of Pendant Stem

 22PENDxx 14" w	 32PENDxx 28" w	 42PENDxx 28" x 28"	
--	--	--	--

SHADE ACCESSORIES

	
VTS	200 / 9 3/4"



ACCESSORIES

 CBC	 PC	 SC	 SLC
 SQ	 SWL	 TBK	

GLASS

 CL (Clear)	 FR (Frosted)
 PR (Prismatic)	 BLU (Blue)
 AMB (Amber)	 GRN (Green)
 RED (Red)	

GUARDS

 GUPC 200	 GUP 200
--	---

Driver Housing

 RTC	
 RTCNC	